

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 July 2003 (17.07.2003)


PCT

(10) International Publication Number
WO 03/058260 A1

- (51) International Patent Classification⁷: **G01R 1/073**
- (21) International Application Number: **PCT/DK03/00006**
- (22) International Filing Date: **7 January 2003 (07.01.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
PA 2002 00020 7 January 2002 (07.01.2002) DK
- (71) Applicant (for all designated States except US): **CAPRES A/S [DK/DK]; c/o MIC, DTU Bygn. 345 Øst, DK-2800 Lyngby (DK).**
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **PETERSEN, Christian, Leth [DK/CA]; #204-488 West 40th Avenue, Vancouver, British Columbia CA-V5Y 2R4 (CA). NIELSEN, Peter Folmer [DK/DK]; Nordtoftevej 31, DK-3520 Farum (DK).**
- (74) Agent: **NIELSEN, Henrik Sten; BUDDE, SCHOU & OSTENFELD A/S, Vester Søgade 10, DK-1601 Copenhagen V (DK).**
- (81) Designated States (national): **AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**

[Continued on next page]

(54) Title: **ELECTRICAL FEEDBACK DETECTION SYSTEM FOR MULTI-POINT PROBES**



(57) Abstract: An electrical feedback detection system for detecting electrical contact between a multi-point probe and an electrically conducting material test sample surface. The electrical feedback detection system comprises an electrical detector unit connected to a multitude of electrodes in the multi-point probe, and optionally directly to the test sample surface. The detector unit provides an electrical signal to a multi-point testing apparatus, which can be used to determine if the multi-point probe is in electrical contact with the test sample surface. The detector unit comprises an electrical generator means for generating an electrical signal that is driven through a first multitude of electrodes of the multi-point probe, and a second multitude of switched impedance detection elements. The electrical potential across the impedance detection elements determines the electrical contact to the test sample surface.

03/058260 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

ELECTRICAL FEEDBACK DETECTION SYSTEM FOR MULTI-POINT PROBES

The present invention generally relates to an electrical feedback detection system for detecting physical contact and/or close proximity between a multi-point probe and an locally electrically conducting, semi-conducting or super-conducting material test sample surface and further relates to the technique of controlling the relative position of a multi-point probe and a material test sample surface, and in particular to an electrical feedback detection system for the multi-point probe and multi-point testing apparatus described in European Patent Application EP 98610023.8 (Petersen), International Patent Application PCT/DK99/00391 (Capres ApS et al), European Patent Application EP 99932677.0 (Capres ApS), European Patent Application EP 99610052.5 (Petersen et al), and International Patent Application PCT/DK00/00513 (Capres Aps et al).

Description of the related art

A scanning tunneling microscope involving controlled approach of a single tip electrode towards a conducting sample surface is well known from the literature; see for example Binnig and Rohrer, *Scanning tunneling microscopy*, Helv. Phys. Acta, vol. 55, pg. 355 (1982). The scanning tunneling microscope consists of a conducting sample and tip, as shown in figure 1(a). If the tip and the sample are separated by a very short distance d and a potential V exists between them, a tunneling current

$$I \propto e^{-\sqrt{\phi}d},$$

is running between the tip and sample, ϕ being the average work function of the materials. If the distance d is on the order of 1nm, a detectable current can be generated. Figure 1(b) shows a schematic of a complete scanning tunneling apparatus capable of positioning the tip within tunneling distance from the test sample at different test locations, thereby generating maps of nanometer scale topographic and electrical features of the test sample.

Figure 2(a)-(b) shows a schematic of the conventional four-point probe (see for example S.M. Sze, Semiconductor devices – Physics and Technology, Wiley New York (1985), and published international patent application WO 94/11745). The conventional four-point probe consists of four electrodes in an in-line configuration as shown in figure 2(a). By applying a current to the two peripheral electrodes, a voltage can be measured between the inner two electrodes. This allows the electric sheet resistivity of a test sample to be determined through the equation

$$\rho = c \cdot (V/I),$$

wherein V is the measured voltage and I is the applied current and wherein c is a geometry factor determined by the electrode separation of the four-point probe and the dimensions of the test sample. A principle diagram of the electronic circuit connected to the four-point probe is shown in figure 2(b).

Figure 3(a)-(b) shows a schematic of a conventional microscopic multi-point probe (see for example published European patent application EP 1 085 327 A1). Figure 3(a) shows the multi-point probe, consisting of a supporting body and a multitude of conductive probe arms freely extending from the base of the supporting body. Figure 3(b) shows a multi-point testing apparatus that implement the mechanical

and electrical means for using the microscopic multi-point probe for measuring the electric properties of a test sample.

An object of the present invention is to provide a novel electrical detector mechanism allowing the detection of physical or otherwise electrical contact

5 between a multi-point probe and a sample test material surface.

A particular advantage of the present invention is related to the fact that the novel electrical detector mechanism allows the detection of electrical connection between a multitude of multi-point probe electrodes, thereby giving information of the electrical contact of a multitude of electrodes of the multi-point probe.

10 A particular feature of the present invention is that the novel electrical detector mechanism does not require a macroscopically conducting sample surface, thereby providing detection of electrical contact to any material surface that contains a local electrical path between several electrodes of the multi-point probe at a specific location of the multi-point probe.

15 The above object, the above advantage and the above feature together with numerous other advantages and features which will be evident from the below detailed description of a preferred embodiment of the present invention is according to the present invention obtained by a electrical feedback control system for detecting electrical contact to a specific location of a test sample, comprising:

20

(a) Electric generator means connected to a first multitude of electrodes of a multipoint probe;

(b) A second multitude of switched impedance detection elements connecting said first multitude of electrodes of said multipoint probe; and

(c) Electrical detector means for detecting a measuring signal from the electrical signal across said second multitude of switched impedance detection elements.

5

The technique characteristic of the present invention of detecting contact between a multi-point probe and the test locations of a test sample by utilizing an electrical signal flowing in the multi-point probe electrodes avoids the use of laser deflection detection mechanisms in the case of microscopic cantilever based multi-point electrodes, which is a dramatic simplification of the conventional optical feedback control systems for microscopic cantilever based testing apparatus such as Atomic Force Microscopes and Scanning Resistance Microscopes.

10

The electric generator means connected to a first multitude of multi-point probe electrodes according to the present invention sends a generator signal through the test sample at the test location, that being current or voltage, pulsed signal or signals, DC or AC having sinusoidal, square, triangle signal content or combinations thereof, ranging from LF to HF, in accordance with specific detection requirements such as sensitivity to resistance, inductance, capacitance or combinations thereof, having a LF sinusoidal AC current signal as the presently preferred embodiment.

15

The first multitude of electrodes of a multi-point probe according to the present invention ranges from at least two electrodes to 64 electrodes, having the two peripherally positioned electrodes of the multi-point probe as the present preferred embodiment. Application of a generator signal to two peripherally positioned electrodes of the multi-point probe provides a resultant detector signal over the second multitude of impedance detection elements according to the present

20

25

invention, and infers information about the electrical contact conditions of a third multitude of the multi-point probe electrodes. An electrical contact condition can involve physical contact, tunneling proximity, intermediate fluid meniscus, or any other effect allowing electrical current to flow between the multi-point probe electrodes and the test sample.

The second multitude of switched impedance detection elements according to the present invention ranges from one to ten, having three as the present preferred embodiment. The nominal values of the resistive part of the impedance detection elements ranges from $1\text{m}\Omega$ to $100\text{G}\Omega$, having $1\text{k}\Omega$, $10\text{k}\Omega$ and $100\text{k}\Omega$ as the presently preferred embodiment.

The electrical detector means measures an electrical signal across the second multitude of impedance detection elements according to the present invention, having a sensitive electrometer connected to a phase-locked lock-in amplifier as the preferred embodiment.

Brief description of the drawings

Additional objects and features of the present invention will be more readily apparent from the following detailed description and appended claims taken in conjunction with the drawings, in which:

Fig. 1(a)-(b), provides an overall illustration of the conventional scanning tunneling microscope. (a), a schematic of the tunneling region between a conducting tip and a test sample. (b), a view schematically showing a conventional scanning tunneling apparatus;

Fig. 2(a)-(b), provides a schematic illustration of the conventional four-point probe.

(a), shows a schematic of a conventional four-point probe in electrical contact with a test sample. (b), shows an electrical schematic of a current source and electrometer connected to a conventional four-point probe;

5

Fig. 3(a)-(b), shows an overall illustration of the conventional multi-point probe and testing apparatus. (a), shows the multi-point probe electrodes. (b), is a schematic of the multi-point testing apparatus;

10 Fig. 4, shows a schematic view of the electrical feedback detection system according to the present invention;

Fig. 5(a)-(b), shows an embodiment of the electrical feedback detection system according to the present invention, in which a multi-point probe is not electrically
15 connected a test sample. (a), shows the detailed electrical configuration of the electrical feedback detection system. (b), shows the equivalent electrical diagram of the system;

Fig. 6(a)-(b), shows an embodiment of the electrical feedback detection system according to the present invention, in which a multi-point probe is in electrical
20 contact with a test sample. (a), shows the detailed electrical configuration of the electrical feedback detection system. (b), shows the equivalent electrical diagram of the system;

Fig. 7(a)-(b), shows embodiments of the electrical feedback detection system according to the present invention in which the feedback detection system includes a generator of constant electrical current. (a), shows a single switched impedance detection element in the control circuit. (b), shows a multitude of switched impedance detection elements in the control circuit;

Fig. 8, shows an embodiment of the electrical feedback detection system according to the present invention in which the feedback detection system includes a generator of constant electrical current, and the detector signal is measured between a multitude of the multi-probe electrodes and the test sample material;

Detailed description of the preferred embodiments

A preferred embodiment is directed towards making an electrical feedback detection system for a multi-point probe and is described with respect to figures 4-8.

Figure 4 shows a schematic of a multi-point testing apparatus **100** employing an electrical feedback detection system. The apparatus consists of a multi-point probe **102** in proximity to a test sample **104** which can be moved by a motor stage **108** by means of a controller **106**. The peripherally positioned electrodes of the multi-point probe is connected to an electrical feedback detection system **110**, which is capable of determining if the multi-probe **102** is in electrical contact with the test sample **104**. A detector signal **112** is provided from the electrical feedback detection system **110** to the controller **106**, to enable a controlled positioning and measurement with the multi-point probe **102** at test locations on the test sample **104**.

Figure 5(a)-(b) and 6(a)-(b) together shows the principle of a preferred embodiment of the present invention. Figure 5(a)-(b) shows a principle of the electrical

configuration of the electrical feedback detection system **300** according to the invention, in a situation where no electrical contact exists between the multi-point probe **302** and the test sample **304**. An electrical generator means generates a constant electrical current I_c , and is connected to the peripheral electrodes **302a** and **302b** of the multi-point probe **302**. A impedance detection element consisting of resistive detection element **R** is connected to the circuit through closed switch **SW**, and the electrical potential V_r across the resistive detection element **R** is measured by amplifier circuit **A**. The equivalent electrical diagram of feedback detection system according to the invention in the situation depicted in figure 5(a), is shown in figure 5(b). The constant current I_c runs through the resistive detection element **R**, thereby generating a potential difference

$$V_r = R \cdot I_c,$$

Which is measured by amplifier **A**, and presented at the output of the feedback detection system. Figure 6(a)-(b) shows a schematic diagram and equivalent circuit of the feedback detection system **500** in the case where the multipoint probe **502** is in electrical contact with the surface of the test sample **504**. The electrical generator means is connected to the peripherally positioned electrodes **502a** and **502b** of the multi-point probe **502**. A generated current I_c flows in part through the closed switch **SW** and the resistive detection element **R** and the corresponding electrical potential V_r is measured by the amplifier circuit **A**, and in part through the test sample **504** represented by unknown resistive element R_x . In this case the potential difference V_r is

$$V_r = (R \cdot R_x) / (R + R_x) \cdot I_c.$$

With reference to figures 5 and 6 it is thus established that the introduction of electrical contact between a multi-point probe and a test sample generates a well-defined change in the output of the feedback detection system, hence allowing the detection of changes in the contact condition of a multi-point probe and a test sample.

In a preferred embodiment of the present invention the constant current generated by an electric generator means I_c is $1\mu\text{A}$ and the resistive detection element R has nominal value $100\text{k}\Omega$, and hence the detector signal V_r is 10V if no electrical contact is established between the multi-point probe and the test sample. If electrical contact exists to the test sample, the electrical properties of the test sample give rise to an effective resistance R_x of the test sample. The following table shows the resulting detector signal V_r for a range of different effective resistance values R_x for the test sample:

R_x	V_r	Relative change in V_r from situation of no electrical contact
10Ω	$9.99\mu\text{V}$	1,100,000
$10\text{k}\Omega$	9.99mV	1,100
$1\text{M}\Omega$	909mV	11
$100\text{M}\Omega$	9.09V	1.1

This shows that the electrical feedback detection system is in this particular preferred embodiment of the present invention able to detect contact to test samples with effective electrical resistances in the range from 10Ω to $100\text{M}\Omega$. In a preferred embodiment of the present invention the detector signal is used by the controller of

a multi-point testing apparatus to determine the electrical contact condition of a multi-point probe to a test location of a test sample, and to actively change the contact condition by means of electrical signals to a motor stage defining the relative position of the multi-point probe and the test sample.

- 5 Figure 7(a)-(b) shows detailed implementations of preferred embodiments of the present invention. In figure 7(a), an electrical feedback detection system according to the invention **700** has the peripherally positioned electrodes **702a** and **702b** of a multi-point probe **702** connected to a differential voltage to current converter consisting of amplifier **G**, resistive detection element **R_{set}** and voltage follower **A1**.
- 10 The resistive detection element **R** is connected to the output of the voltage to current converter through switch **SW**. The output of the voltage to current converter is proportional to the voltage difference **V₁-V₂**. The detector signal **V_r** is measured by means of amplifier **A2**. The current **I_c** from the voltage to current converter is sent through the closed switch **SW** and the resistive detection element **R** and through the
- 15 unknown effective resistance **R_x** in the test sample **704**. Figure 7(b) shows an electrical feedback detection system according to the invention **800** with multi-point probe **802** connected to test sample **804** and electrical feedback detection circuit connected to the peripheral electrodes **802a** and **802b** of the multi-point probe **802**. The electrical feedback detection circuit contains a multitude of resistive detection
- 20 elements **R₁** and **R₂**, which can be individually switched into the signal path of the electric generator means by means of switch **SW**, preferable application having three said resistive detection elements with nominal values in the range 100Ω to 10MΩ.


- Figure 8 shows another preferred embodiment of an electrical feedback detection
- 25 system according to the present invention **1000**, with multi-point probe **1002**

connected to test sample **1004** and electrical feedback detection circuit connected between the peripheral electrodes **1002a** and **1002b** of the multi-point probe **1002**, and test sample **1004**. The generated current I_c runs in part through the test sample **1004**, and this gives rise to a change in detector signal V_r across a resistive
5 detection element **R**, even when only one of the multitude of multi-point probe electrodes is in electrical contact with the test sample.


CLAIMS

1. An electrical feedback detection system for detecting electrical contact of a multi-point probe to a material test sample surface comprising:
 - a. Electric generator means connected to a first multitude of electrodes of a multi-point probe;
 - b. A second multitude of switched impedance detection elements connecting said first multitude of electrodes of said multi-point probe; and
 - c. Electrical detector means for detecting a measuring signal from the electrical signal across said second multitude of switched impedance detection elements.
2. An electrical feedback detection system for detecting electrical contact of a multi-point probe to a electrically conducting material surface according to claim 1 further comprising an electrical connection between said electric generator means to said material test sample surface.
3. An electrical feedback detection system for detecting electrical contact of a multi-point probe to a electrically conducting material surface according to claim 1-2 in which the electric generator means is a differential voltage to current converter comprising:
 - a. A precision amplifier providing two differential inputs, one output, and one reference input;
 - b. A precision resistive element providing an internal and external port, said internal port connected to said output of said precision amplifier, and;

1/8




(a)




(b)

PRIOR ART

FIG. 1



(a)




(b)

PRIOR ART


FIG. 2

Multi-point probe

Electrodes




(a)




(b)


PRIOR ART

FIG. 3

**FIG. 4**




(a)




(b)

FIG. 5



(a)



(b)

FIG. 6





FIG. 7




FIG. 8

INTERNATIONAL SEARCH REPORT

International Application No

PCT/DK 000006

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01R1/073

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 1 085 327 A (PETERSEN CHRISTIAN LETH ;BOGGILD PETER (DK); GREY FRANCOIS (DK); Q) 21 March 2001 (2001-03-21) figure 7	1-6
Y	US 5 627 522 A (HILLS DAVID B ET AL) 6 May 1997 (1997-05-06) column 40, line 47-67	1-6
A	US 5 214 389 A (CAO BEATRICE M ET AL) 25 May 1993 (1993-05-25) column 4, line 27-65	1-6
A	US 6 091 248 A (HELLEMANS LOUIS C ET AL) 18 July 2000 (2000-07-18) column 4, line 42-65	1-6
	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 March 2003

Date of mailing of the international search report

03.04.03

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

STURE ELNÄS/JA A

INTERNATIONAL SEARCH REPORT

International Application No

PC7DK 0006

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 01 90730 A (CHERAN LARISA EMILIA ;SENSORCHEM INTERNAT CORP (CA); THOMPSON MICH) 29 November 2001 (2001-11-29) page 3, line 3-16 -----</p>	1-6

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/DK 000006

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1085327	A	21-03-2001	EP 1085327 A1	21-03-2001
			WO 0120347 A1	22-03-2001
			US 2002153909 A1	24-10-2002

US 5627522	A	06-05-1997	US 5376313 A	27-12-1994
			AT 220799 T	15-08-2002
			AU 7843194 A	10-04-1995
			CA 2172363 A1	31-03-1995
			EP 1028320 A2	16-08-2000
			EP 1205756 A2	15-05-2002
			EP 0720747 A1	10-07-1996
			JP 9503060 T	25-03-1997
			WO 9508774 A2	30-03-1995
			US 5646049 A	08-07-1997
			US 5635364 A	03-06-1997
			US 5605665 A	25-02-1997
			US 5575978 A	19-11-1996
			US 5536471 A	16-07-1996
			US 5507410 A	16-04-1996
			US 5610069 A	11-03-1997
			US 5960160 A	28-09-1999
			US 5578494 A	26-11-1996
			US 5762878 A	09-06-1998
			US 6096561 A	01-08-2000
			US 6190617 B1	20-02-2001
			AU 3929093 A	08-11-1993
			AU 3934393 A	08-11-1993
			AU 3934993 A	08-11-1993
			AU 3935093 A	08-11-1993
			AU 3967793 A	08-11-1993
			AU 3968093 A	08-11-1993
			CA 2129245 A1	14-10-1993
			CA 2129246 A1	14-10-1993
			CA 2129367 A1	14-10-1993
			CA 2129368 A1	14-10-1993
			CA 2132959 A1	14-10-1993
			CA 2132960 A1	14-10-1993
			DE 69329147 D1	07-09-2000
			DE 69329147 T2	07-06-2001
			DE 69329276 D1	28-09-2000
			DE 69329276 T2	12-04-2001
			DE 69330785 D1	25-10-2001
			DE 69330785 T2	20-06-2002
			EP 0755519 A1	29-01-1997
			EP 0634016 A1	18-01-1995
			EP 0637283 A1	08-02-1995
			EP 0746769 A1	11-12-1996
			EP 0632894 A1	11-01-1995
			EP 0632896 A1	11-01-1995
			ES 2164071 T3	16-02-2002
			ES 2150442 T3	01-12-2000
			ES 2150942 T3	16-12-2000
			JP 7505473 T	15-06-1995
			JP 3003118 B2	24-01-2000

US 5214389	A	25-05-1993	NONE	

US 6091248	A	18-07-2000	NL 9401390 A	01-04-1996

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 00/00006

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
US 6091248	A	US 5723981 A	03-03-1998	
		US 5585734 A	17-12-1996	
		US 6201401 B1	13-03-2001	

WO 0190730	A	29-11-2001	CA 2309412 A1	24-11-2001
			AU 6194701 A	03-12-2001
			AU 6194801 A	03-12-2001
			WO 0190749 A2	29-11-2001
			WO 0190730 A2	29-11-2001
			EP 1295119 A2	26-03-2003
